



Vivid Step



Vivid Step draws inspiration from natural wood and stone visuals and features colors ranging from rich warm browns to cool grays. The aesthetically flexible shades and textures are designed to fit any interior. Vivid Step's fusion of ultra-modern character and natural beauty add depth and dimension to a traditional flooring solution.





Vivid Step Wood 863 Roasted Kaffee
Cover: Vivid Step Wood 128 Shimmering Sand, Vivid Step Stone 928 Charcoal Grey, Tactile Infusion 739 Diorite

*Transition to be used at all flooring adjacencies.



Interdeco™

Textural Effects COORDINATING CARPET TILE

Textural Effects aims to activate our senses and brings a sense of tactility to our day. The desire for soft groundcover visuals such as linen textiles and organic patterns are met with tactility and comfort to sustain us in all types of spaces. All Textural Effects styles provide visual and tactile contrast when used with other finishes that have a smooth surface or high gloss, and they look especially warm and rich with wood hard surfaces.

FEATURES

- Available in two styles: Tactile Infusion and Thematic Thread
- 12" x 36" Carpet Planks
- Duracolor® Tricor Premium Nylon
- EcoFlex™ NXT Backing
- NSF/ANSI 140 Gold
- Living Product Challenge Petal Certified
- Declared Red List Free, EPD and HPD



Tactile Infusion 967 Granite



Vivid Step Wood & Stone

FEATURES

- 12 Wood colorways and 4 Stone colorways
- Enhanced Urethane finish for wear and scratch resistance
- No-polish maintenance reduces costs associated with long-term cleaning
- Designed to coordinate with a variety of Mohawk Group carpet collections
- FloorScore® certified



Vivid Step Wood Colorways



128 Shimmering Sand



132 Grounded Hatch




989 Perfect Portobello



979 Deep Gris



863 Roasted Kaffee



754 Sable Birch



959 Turkish Blend



898 Java Hut



746 Beary Brown



723 Vintage Oak




719 Candied Pecan



236 Golden Pine

Vivid Step Stone Colorways



928 Charcoal Grey



919 Carrara Stone



999 Stormy Nights



142 Moon Walk

Specifications

Vivid Step Wood CR705
Vivid Step Stone CR706

DESIGN

Size	
Vivid Step Wood	Nominal 6" x 48" Actual 152.4mm x 1,210.2mm
Vivid Step Stone	Nominal 12" x 24" Actual 304.8mm x 609.6mm
Overall Thickness	2mm (.079")
Wear Layer	12 mil (0.3mm)
Finish	Enhanced Urethane
Colors Available	
Vivid Step Wood	12
Vivid Step Stone	4
Edge	Bevel
Packaging	
Vivid Step Wood	54 sqft per carton / 27 pcs per carton / 36.55 lbs per carton
Vivid Step Stone	44 sqft per carton / 22 pcs per carton / 29.78 lbs per carton

*For detailed warranty, adhesive and installation information visit mohawkgroup.com

PERFORMANCE

Construction	Light Commercial Grade Dryback Enhanced Resilient Tile
Classification	ASTM F1700 - Class III, Type A - Smooth, Type B - Embossed
Squareness	ASTM F 2421 - Passes - ± 0.10 " max
Size and Tolerance	ASTM F2421 - Passes - ± 0.016 "/linear foot
Thickness	ASTM F386 - Passes - Nominal ± 0.005 "
Flexibility	A ASTM F137 - Passes - 1" mandrel
Dimensional Stability	ASTM F2199 - Passes - ≤ 0.020 "/linear foot
Static Load Limit	ASTM F970 - Passes, modified at 1000 psi
Residual Indentation	ASTM F1914 - Passes - Average less than 8% maximum single reading 10%
Resistance to Chemicals	ASTM F925 - Passes - No change or Slight Change
Resistance to Light	ASTM F1515 - Passes - $\Delta E \leq 8$
Resistance to Heat	ASTM F1514 - Passes - $\Delta E \leq 8$
Critical Radiant Flux	ASTM E648 - Passes - ≥ 0.45 watts/cm ² , Class 1
Smoke Density	ASTM E662 - Passe Part A - Less than 450

SUSTAINABILITY

Certification	FloorScore® Certified
---------------	-----------------------

Mohawk Group

Mohawk Group
160 South Industrial Blvd.
Calhoun, GA. 30701
1-800-554-6637
mohawkgroup.com

CR705 PHOTO BROCHR LT



Vivid Step Wood

Collection	Vivid Step
Style Name	Vivid Step Wood
Style Number	CR705
Product Type	LVT
Size	6" X 48"

Feature	Description
Overall Thickness	2 mm
Wear Layer	12 mil (0.3 mm)
Finish	Enhanced Urethane
Surface Profile	Overall Emboss
Squareness	ASTM F 2421 - Passes - ±0.10" max
Flexibility	ASTM F137 - Passes - 1" mandrel
Square Foot per Carton	54
Pounds per Carton	36.45
Classification	ASTM F1700 - Class III, Type B - Embosse



Recommended Installation Methods



Monolithic




Monolithic Stepping



Half Lap



Random



Brick Ashlar



Herringbone

Colorways



Shimmering Sand

Color code: W128
Style number: CR705



Grounded Hatch

Color code: W132
Style number: CR705



Golden Pine

Color code: W236
Style number: CR705



Candied Pecan

Color code: W719
Style number: CR705



Vintage Oak

Color code: W723
Style number: CR705



Beary Brown

Color code: W746
Style number: CR705



Sable Birch

Color code: W754
Style number: CR705



Roasted Kaffee

Color code: W863
Style number: CR705



Java Hut

Color code: W898
Style number: CR705



Turkish Blend

Color code: W959
Style number: CR705



Deep Gris

Color code: W979
Style number: CR705



Perfect Portobello

Color code: W989
Style number: CR705



Performance

Feature	Description
Static Load	ASTM F970 - Passes, modified at 1000 psi
Residual Indentation	ASTM F1914 - Passes - Average less than 8% maximum single reading 10%
Resistance to Chemicals	ASTM F925 - Passes - No more than a slight change
Resistance to Heat	ASTM F1514 - Passes - ΔE <8
Resistance to Light	ASTM F1515 - Passes - ΔE <8
Critical Radiant Flux	ASTM E648 - Class 1 (>0.45 W/cm ²)
Smoke Density	ASTM E662 Part A - Less than 450

Sustainability

Feature	Description
Floor Score	Floor Score Certified
Mindful Materials	Participates in Mindful Materials Library
Environmental Product Declaration	EPD Vinyl Tile
Beyond Carbon Neutral	This product is 100% carbon neutral plus an additional 5% offset
Carbon Handprint	-0.055 kg CO ₂ e/ft ²
Embodied Carbon	1.11 kg CO ₂ e/ft ²

Warranties

Limited 10 Year Light Commercial Warranty

Vivid Step Stone

Collection	Vivid Step
Style Name	Vivid Step Stone
Style Number	CR706
Product Type	LVT
Size	12" X 24"

Feature	Description
Overall Thickness	2 mm
Wear Layer	12 mil (0.3 mm)
Finish	Enhanced Urethane
Surface Profile	Overall Emboss
Squareness	ASTM F 2421 - Passes - ±0.10" max
Flexibility	ASTM F137 - Passes - 1" mandrel
Square Foot per Carton	44
Pounds per Carton	28.82
Classification	ASTM F1700 - Class III, Type B - Embosse



Recommended Installation Methods



Monolithic




Monolithic Stepping



Half Lap



Random



Brick Ashlar



Herringbone

Colorways



Moon Walk

Color code: S142
Style number: CR706



Carrara Stone

Color code: S919
Style number: CR706



Charcoal Grey

Color code: S928
Style number: CR706



Stormy Nights

Color code: S999
Style number: CR706

Performance

Feature	Description
Static Load	ASTM F970 - Passes, modified at 1000 psi
Residual Indentation	ASTM F1914 - Passes - Average less than 8% maximum single reading 10%
Resistance to Chemicals	ASTM F925 - Passes - No more than a slight change
Resistance to Heat	ASTM F1514 - Passes - Δ E <8
Resistance to Light	ASTM F1515 - Passes - Δ E <8
Critical Radiant Flux	ASTM E648 - Class 1 (>0.45 W/cm ²)
Smoke Density	ASTM E662 Part A - Less than 450



Sustainability

Feature	Description
Floor Score	Floor Score Certified
Mindful Materials	Participates in Mindful Materials Library
Environmental Product Declaration	EPD Vinyl Tile

Warranties

Limited 10 Year Light Commercial Warranty